

Hřídél pro uzavírací klapky

Popis

Údržba našich ventilů musí být prováděna podle našich postupů, které jsou k dispozici na vyžádání.

Shaft

#	d (mm)	DN (mm)	DN (inch)
1	63	50	2"
2	75	65	2"1/2
3	90	80	3"
4	110	100	4"
5	140	125	5"
6	160	150	6"
7	225	200	8"
8	280	250	10"
9	315	300	12"
10	355	350	14"
11	400	400	16"
12	450	450	18"
13	500	500	20"
14	630	600	24"
15	710	700	28"
16	800	800	32"
17	900	900	36"
18	1000	1000	40"

Shaft

#	d (mm)	DN (mm)	DN (inch)
1	63	50	2"
2	75	65	2"1/2
3	90	80	3"
4	110	100	4"
5	140	125	5"
6	160	150	6"
7	225	200	8"
8	280	250	10"
9	315	300	12"
10	355	350	14"
11	400	400	16"
12	450	450	18"
13	500	500	20"
14	630	600	24"
15	710	700	28"
16	800	800	32"
17	900	900	36"
18	1000	1000	40"

Shaft

#	d (mm)	DN (mm)	DN (inch)
1	63	50	2"
2	75	65	2"1/2
3	90	80	3"
4	110	100	4"
5	140	125	5"
6	160	150	6"
7	225	200	8"
8	280	250	10"
9	315	300	12"
10	355	350	14"
11	400	400	16"
12	450	450	18"
13	500	500	20"
14	630	600	24"
15	710	700	28"
16	800	800	32"
17	900	900	36"
18	1000	1000	40"

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.
Přeloženo z originálu výrobce.

Farprosys, s.r.o.
email: info@farprosys.com
tel. +420 728 757 770
www.atexventilatory.cz