



Rediff typ AUG 10/N, hrdlové napojení

Popis

difuzor odpadního vzduchu s integrovaným deflektorem

PVC

#	d	d	L	L1	s PVC	s PP-Basis	B1	B2	d3	kg
1	0110m	170	200	40	3,0	3,0	80	-	16	0,5
2	0125m	190	230	40	3,0	3,0	90	-	20	0,6
3	0140m	215	255	40	3,0	3,0	100	-	20	0,8
4	0160m	245	295	40	3,0	3,0	115	-	25	1,0
5	0180m	275	330	50	3,0	3,0	130	-	25	1,3
6	0200m	305	350	50	3,0	3,0	150	-	25	1,5
7	0225m	345	415	50	3,0	4,0	156	-	25	1,9
8	0250m	380	460	60	3,0	4,0	185	-	25	2,4
9	0280m	425	515	50	3,0	4,0	205	-	25	2,9
11	0355m	540	650	50	4,0	5,0	260	-	32	6,2
12	0400m	610	735	70	4,0	6,0	290	-	40	8,1
13	0450m	685	825	65	6,0	6,0	290	-	40	10,1
14	0500m	765	915	100	6,0	6,0	370	410	50	19,0
15	0560m	855	1030	100	6,0	6,0	405	455	50	15,9
16	0600m	915	1100	100	6,0	6,0	450	490	63	27,2
17	0630m	960	1155	100	6,0	6,0	450	490	63	20,0

PPs

#	d	d	L	L1	s PVC	s PP-Basis	B1	B2	d3	kg
1	0110m	170	200	40	3,0	3,0	80	-	16	0,5
2	0125m	190	230	40	3,0	3,0	90	-	20	0,6
3	0140m	215	255	40	3,0	3,0	100	-	20	0,8
4	0160m	245	295	40	3,0	3,0	115	-	25	1,0
5	0180m	275	330	50	3,0	3,0	130	-	25	1,3
6	0200m	305	350	50	3,0	3,0	150	-	25	1,5
7	0225m	345	415	50	3,0	4,0	156	-	25	1,9
8	0250m	380	460	60	3,0	4,0	185	-	25	2,4
9	0280m	425	515	50	3,0	4,0	205	-	25	2,9
11	0355m	540	650	50	4,0	5,0	260	-	32	6,2
12	0400m	610	735	70	4,0	6,0	290	-	40	8,1
13	0450m	685	825	65	6,0	6,0	290	-	40	10,1
14	0500m	765	915	100	6,0	6,0	370	410	50	19,0
15	0560m	855	1030	100	6,0	6,0	405	455	50	15,9
16	0600m	915	1100	100	6,0	6,0	450	490	63	27,2
17	0630m	960	1155	100	6,0	6,0	450	490	63	20,0

PP

#	d	d	L	L1	s PVC	s PP-Basis	B1	B2	d3	kg
1	0110m	170	200	40	3,0	3,0	80	-	16	0,5
2	0125m	190	230	40	3,0	3,0	90	-	20	0,6
3	0140m	215	255	40	3,0	3,0	100	-	20	0,8
4	0160m	245	295	40	3,0	3,0	115	-	25	1,0
5	0180m	275	330	50	3,0	3,0	130	-	25	1,3
6	0200m	305	350	50	3,0	3,0	150	-	25	1,5
7	0225m	345	415	50	3,0	4,0	156	-	25	1,9
8	0250m	380	460	60	3,0	4,0	185	-	25	2,4
9	0280m	425	515	50	3,0	4,0	205	-	25	2,9
11	0355m	540	650	50	4,0	5,0	260	-	32	6,2
12	0400m	610	735	70	4,0	6,0	290	-	40	8,1
13	0450m	685	825	65	6,0	6,0	290	-	40	10,1
14	0500m	765	915	100	6,0	6,0	370	410	50	19,0
15	0560m	855	1030	100	6,0	6,0	405	455	50	15,9
16	0600m	915	1100	100	6,0	6,0	450	490	63	27,2
17	0630m	960	1155	100	6,0	6,0	450	490	63	20,0

PE

#	d	d	L	L1	s PVC	s PP-Basis	B1	B2	d3	kg
1	0110m	170	200	40	3,0	3,0	80	-	16	0,5
2	0125m	190	230	40	3,0	3,0	90	-	20	0,6
3	0140m	215	255	40	3,0	3,0	100	-	20	0,8
4	0160m	245	295	40	3,0	3,0	115	-	25	1,0
5	0180m	275	330	50	3,0	3,0	130	-	25	1,3
6	0200m	305	350	50	3,0	3,0	150	-	25	1,5
7	0225m	345	415	50	3,0	4,0	156	-	25	1,9
8	0250m	380	460	60	3,0	4,0	185	-	25	2,4
9	0280m	425	515	50	3,0	4,0	205	-	25	2,9
11	0355m	540	650	50	4,0	5,0	260	-	32	6,2
12	0400m	610	735	70	4,0	6,0	290	-	40	8,1
13	0450m	685	825	65	6,0	6,0	290	-	40	10,1
14	0500m	765	915	100	6,0	6,0	370	410	50	19,0
15	0560m	855	1030	100	6,0	6,0	405	455	50	15,9
16	0600m	915	1100	100	6,0	6,0	450	490	63	27,2
17	0630m	960	1155	100	6,0	6,0	450	490	63	20,0

PPs-el

#	d	d	L	L1	s PVC	s PP-Basis	B1	B2	d3	kg
1	0110m	170	200	40	3,0	3,0	80	-	16	0,5
2	0125m	190	230	40	3,0	3,0	90	-	20	0,6
3	0140m	215	255	40	3,0	3,0	100	-	20	0,8
4	0160m	245	295	40	3,0	3,0	115	-	25	1,0
5	0180m	275	330	50	3,0	3,0	130	-	25	1,3
6	0200m	305	350	50	3,0	3,0	150	-	25	1,5
7	0225m	345	415	50	3,0	4,0	156	-	25	1,9
8	0250m	380	460	60	3,0	4,0	185	-	25	2,4
9	0280m	425	515	50	3,0	4,0	205	-	25	2,9
11	0355m	540	650	50	4,0	5,0	260	-	32	6,2
12	0400m	610	735	70	4,0	6,0	290	-	40	8,1
13	0450m	685	825	65	6,0	6,0	290	-	40	10,1
14	0500m	765	915	100	6,0	6,0	370	410	50	19,0
15	0560m	855	1030	100	6,0	6,0	405	455	50	15,9
16	0600m	915	1100	100	6,0	6,0	450	490	63	27,2
17	0630m	960	1155	100	6,0	6,0	450	490	63	20,0

PVDF

#	d	d	L	L1	s PVC	s PP-Basis	B1	B2	d3	kg
1	0110m	170	200	40	3,0	3,0	80	-	16	0,5
2	0125m	190	230	40	3,0	3,0	90	-	20	0,6
3	0140m	215	255	40	3,0	3,0	100	-	20	0,8
4	0160m	245	295	40	3,0	3,0	115	-	25	1,0
5	0180m	275	330	50	3,0	3,0	130	-	25	1,3
6	0200m	305	350	50	3,0	3,0	150	-	25	1,5
7	0225m	345	415	50	3,0	4,0	156	-	25	1,9
8	0250m	380	460	60	3,0	4,0	185	-	25	2,4
9	0280m	425	515	50	3,0	4,0	205	-	25	2,9
11	0355m	540	650	50	4,0	5,0	260	-	32	6,2
12	0400m	610	735	70	4,0	6,0	290	-	40	8,1
13	0450m	685	825	65	6,0	6,0	290	-	40	10,1
14	0500m	765	915	100	6,0	6,0	370	410	50	19,0
15	0560m	855	1030	100	6,0	6,0	405	455	50	15,9
16	0600m	915	1100	100	6,0	6,0	450	490	63	27,2
17	0630m	960	1155	100	6,0	6,0	450	490	63	20,0

PVC-UV

#	d	d	L	L1	s PVC	s PP-Basis	B1	B2	d3	kg
1	0110m	170	200	40	3,0	3,0	80	-	16	0,5
2	0125m	190	230	40	3,0	3,0	90	-	20	0,6
3	0140m	215	255	40	3,0	3,0	100	-	20	0,8
4	0160m	245	295	40	3,0	3,0	115	-	25	1,0
5	0180m	275	330	50	3,0	3,0	130	-	25	1,3
6	0200m	305	350	50	3,0	3,0	150	-	25	1,5
7	0225m	345	415	50	3,0	4,0	156	-	25	1,9
8	0250m	380	460	60	3,0	4,0	185	-	25	2,4
9	0280m	425	515	50	3,0	4,0	205	-	25	2,9
11	0355m	540	650	50	4,0	5,0	260	-	32	6,2
12	0400m	610	735	70	4,0	6,0	290	-	40	8,1
13	0450m	685	825	65	6,0	6,0	290	-	40	10,1
14	0500m	765	915	100	6,0	6,0	370	410	50	19,0
15	0560m	855	1030	100	6,0	6,0	405	455	50	15,9
16	0600m	915	1100	100	6,0	6,0	450	490	63	27,2
17	0630m	960	1155	100	6,0	6,0	450	490	63	20,0

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.
Přeloženo z originálu výrobce.

Farprosys, s.r.o.
email: info@farprosys.com
tel. +420 728 757 770
www.atexventilatory.cz